



产品特性/Product Features

- IP6K9K
- 250A 85°C长时间载流能力
- 12-750VDC
- 1000MΩ (1000VDC) , IEC 60664-1
- PWM
- 10000次寿命
- 10000次寿命

触点参数 / Contact parameters

		1a	
		≤0.3mΩ at 250A	
		250A	
		2×10 ⁵	
		450V型	750V型
		750VDC	750VDC
		2000A 320VDC 1	2000A 320VDC 1
		112.5kW	187.5kW
1		5×10 ⁴ 32VDC =1ms, 350A	5×10 ⁴ 32VDC =1ms, 350A
		50 64VDC =1ms, 650A	50 64VDC =1ms, 650A
	1.5×10 ³ 450VDC, 250A	500 750VDC, 250A	
	500 450VDC, -250A	100 750VDC, -250A	
	1 320VDC, 2000A	1 320VDC, 2000A	
2		250A:	
		320A:10min	
		500A:1min	
		2000A:1s	
辅助触点			1NO
	Ue	30VDC/125VAC	
		2A DC /3A AC	
		9V0.1A	

1) 23°C, 0.6s:5.4s.

2) 85°C, 100 mm².

性能参数 / Performance parameters

		1000MΩ(1000VDC)
		3000VAC 1min
		3000VAC 1min
()		≤30ms
()		≤10ms
		196m/s ²
		490m/s ²
		10Hz~500Hz 49m/s ²
		5%~85%RH
		-40°C~85°C
		/
		400g

线圈参数 / Coil parameter

9~24V	9	≥4.5	
			-40°C~85°C)

外形尺寸

/Unit mm

